

# A COMPLETE LINE OF SHINGLE UNDERLAYMENTS

**ROOFERS' SELECT™** Made to order for the true professional

Contractors across the country told us what they wanted in a high quality shingle underlayment. We've taken new technology and created Roofers' Select™, an underlayment with high performance features which exceed No. 15 organic felt and are comparable to No. 30 organic felt.

## Features

- Lays flat and is extremely resistant to wrinkling.
- Reduces the likelihood of slipping for increased safety.
- Doesn't tear away from fasteners when walked on or in strong winds.
- Meets underlayment requirements for the CertainTeed Integrity Roof System™.

## Technical Data

Roll size (sq. ft.)	432 (4 squares)
Roll coverage (sq. ft.)	400
Roll length (ft.)	144
Roll width (ft.)	3
Shipping weight (approx. lbs./roll)	44

Manufactured to meet all performance requirements of ASTM D226 and ASTM D4869, including resistance to "liquid water transmission."  
Manufactured to comply with ASTM D6757. Classified by UL to be a suitable underlayment for use in any UL Class A, B, or C fire-rated shingle system.



## ROOFWRAP™ 15 / ROOFWRAP™ 30

### UL classified for fire-rated shingle systems

RoofWrap™ 15 and RoofWrap™ 30 are asphalt-impregnated underlayments that meet key industry performance criteria, including ASTM D226 and ASTM D4869, and are UL classified for fire-rated shingle systems. They provide a water-resistant layer beneath roofing shingles and wood shakes, and meet underlayment requirements for the Integrity Roof System.

### Technical Data

	RoofWrap 15	RoofWrap 30
Roll size (sq. ft.)	432 (4 squares)	216 (2 squares)
Roll coverage (sq. ft.)	400	200
Roll length (ft.)	144	72
Roll width (ft.)	3	3
Shipping weight (approx. lbs./roll)	53	56
ASTM D226	Type I	Type II
ASTM D4869	Type I	Type II
Underwriters Laboratories, Inc. (UL)	Type 15	Type 30

Both products are classified by UL to be a suitable underlayment for use in any UL Class A, B, or C fire-rated shingle system.



## SHINGLEFELT™ 15 / SHINGLEFELT™ 30

### A basic underlayment

ShingleFelt™ 15 and ShingleFelt™ 30 utility-grade underlayments comply with the important ASTM D4869 standard, yet are lighter and more economical than competing products. They provide a water-resistant layer beneath roofing shingles and wood shakes.

### Technical Data

	ShingleFelt 15	ShingleFelt 30
Roll size (sq. ft.)	432 (4 squares)	216 (2 squares)
Roll coverage (sq. ft.)	400	200
Roll length (ft.)	144	72
Roll width (ft.)	3	3
Shipping weight (approx. lbs./roll)	39	28
ASTM D4869	Type I	Type I



For more information visit [www.certainteed.com](http://www.certainteed.com) or call 1-800-233-8990

